



FALKEN  
Secure Networks

Durable RFID tags and labels for any environment

## Domed RFID Labels

Short or Long Run Orders • Unique Solutions • Harsh Environment Encapsulations



**Part Number:** WF-SM-04

**Size:** 4" dia. Circle

**Standard Frequencies:** 915 MHz UHF

**Approx. Read Range:** 8 ft.

**Communication Protocol:**  
EPC Class1 Generation 2

**Applications:** High-Visibility, Corporate Branding, Product Identification

**Description:** Domed labels provide an attractive way to provide both visual and RFID identification.

Designed to accommodate a wide variety of inlays and antennas, they can be coupled with special backings to allow use on metal. Adhesive backings provide peel-and-stick convenience.

**Sizes and shapes can be adjusted to allow other inlays, frequencies and applications.**



**Part Number:** WF-SM-05

**Size:** 4.25" x 4" x .0625"

**Standard Frequencies:** 915 MHz UHF

**Approx. Read Range:** 16 ft.

**Communication Protocol:** EPC Class1Gen 2

**Applications:** Manholes, Roadside Curb Marking, Outdoor Assets

**Description:** Domed labels provide an attractive way to provide both visual and RFID identification. Designed to accommodate a wide variety of inlays and antennas, they can be coupled with special backings to allow use on metal. Adhesive backings

provide peel-and-stick convenience and long-lasting epoxy adhesives are also available.

**Sizes and shapes can be adjusted to allow other inlays, frequencies and applications.**



**Part Number:** WF-SM-18

**Size:** 1.75" dia. Circle

**Standard Frequencies:** 13.56 MHz HF

**Approx. Read Range:** 5-12 inches

**Communication Protocol:** ISO 15693

**Applications:** High-Visibility, Corporate Branding, Warranty Verification, Product Identification

**Description:** Domed labels provide an attractive way to provide both visual and RFID identification. Designed to accommodate a wide variety of inlays and antennas, they can be coupled with special backings to allow use on metal. Adhesive backings provide peel-and-stick convenience.

**Sizes and shapes can be adjusted to allow other inlays, frequencies and applications.**



**Part Number:** WF-SM-26

**Size:** 2.75" x .875" x .1875"

**Standard Frequencies:** 915 MHz UHF

**Approx. Read Range:** 5-7 inches

**Communication Protocol:** Class1 Generation 2

**Applications:** High-Visibility, Corporate Branding, Warranty Verification, Product Identification

**Description:** Domed labels provide an attractive way to provide both visual and RFID identification. Designed to accommodate a wide variety of inlays and antennas, they can be coupled with special backings to allow use on metal. Adhesive backings provide peel-and-stick convenience.

**Sizes and shapes can be adjusted to allow other inlays, frequencies and applications.**

## Contact Information:

*Call today for all your custom RFID needs:*

**David Kennedy, VP and Gen. Mgr. Phone: (519) 268-7604;**

**E-mail: david.kennedy@falkensecurenetworks.com**

**Web: www.falkensecurenetworks.com**