



Encapsulated Tags



Short or Long Run Orders • Unique Solutions • Harsh Environment Encapsulations



Part Number: WF-SM-02

Size: 2.75" x 2.75" x .1875"

Standard Frequencies:
13.56 MHz

Approx. Read Range:
6-12 inches

Communication Protocol:
ISO 15693

Applications: Warehouses,
Transportation, Vehicles, Harsh
environments

Description: Built of durable plastic, this
molded tag is tailored for near field reads
for access control applications. Its design

can easily accommodate a wide variety of inlays and antennas and it can be mounted securely to nearly any surface using the integrated screw/rievet holes. Customize with your logo, specific information or barcodes.

Size and shape can be adjusted to allow other inlays, frequencies and applications.



Part Number: WF-SM-12

Size: 5" x 3.125" x .375"

Standard Frequencies: 915 MHz UHF

Approx. Read Range: 18 ft. / 4 ft. on metal

Communication Protocol:
EPC Class1 Generation 2

Applications: Warehouses, Pallets, Transportation,
Harsh environments

Description: Built of durable plastic, this
molded tag is perfect for metal bins & pallets
and delivers reliable performance on a

variety of surfaces including plastic, wood and metal. Designed to accommodate a wide variety of inlays and antennas, it can be mounted securely to nearly any surface using the integrated screw/rivet holes. **Size and shape can be adjusted to allow other inlays, frequencies and applications.**



Part Number: WF-SM-28

Size: 4.75" x 1.75" x .3125"

Standard Frequencies: 915 MHz UHF

Approx. Read Range: 21 ft. / 3 ft. on metal

Communication Protocol: EPC Class1 Generation 2

Applications: Warehouses, Transportation, Vehicles, Harsh Environments

Description: Built of durable plastic, this molded tag delivers reliable performance on a variety of surfaces including plastic, wood and metal. Designed to accommodate a wide variety of inlays and antennas, it can be mounted securely to nearly any surface using the integrated screw/rivet holes. Include your own logo, message or barcode.

Size and shape can be adjusted to allow other inlays, frequencies and applications.



Part Number: WF-SM-UTS

Size: 7" x 2.75" x .75"

Standard Frequencies:
915 MHz UHF or tuned to your specs

Approx. Read Range: 25 ft. / 8 ft. on metal

Communication Protocol:

Applications: Warehouses, Pallets,
Aisle Markers, Embedded

Description: Designed as a reusable universal rugged tagging solution, these tags

are available with a wide variety of bases for use in nearly any setting. Perfect for applications that require embedding in concrete or semi-permanent RFID installations, they can quickly and easily be tailored to your application and mounted on a wide variety of surfaces including metal, wood, or plastic.

Contact Information:

Call today for all your custom RFID needs:

David Kennedy, VP and Gen. Mgr. Phone: (519) 268-7604;

E-mail: david.kennedy@falkensecurenetworks.com

Web: www.falkensecurenetworks.com