

For Fast and Intuitive Digital Workflow

Work Directly On Screen

The DTU-1031 is the ideal solution for environments that require a pen display with minimal footprint. The thin, compact form factor can be used on even the smallest podiums or desk, while Wacom's pen provides an industry-leading experience for natural and responsive writing and drawing to mark up and annotate over existing content or integrate input and new ideas from others. It's use of a single USB cable to provide video, power and USB data makes it easy to integrate into new or existing facilities.



Key Features

- 10.1" IPS color, wide viewing angle LCD display with 1280 x 800 resolution and LED backlight.
- Single USB cable installation. USB cable supplies video, power and USB data.
- Cordless and battery-free pen with 2 side-switches, 512 levels of pressure sensitivity for premium writing experience.
- Slim profile allows it to be used flat on the desktop.
- 4 user-assignable ExpressKeys can be assigned to common functions and tools.
- Hardened, anti-glare surface provides high durability and easier viewing in different lighting conditions.
- VESA mounting holes allow you to use third-party arms and stands.

For more information:

<http://www.wacom.com>



FALKEN Secure Networks Inc. is an Authorized Value-Added Reseller of WACOM and XYZMO.

General		Display	
Dimensions	12.2"W x 8.3"H x 0.6"D (excluding stand)	Type	IPS LCD
Weight	2.2 lbs. (including stand)	Screen size	10.1" diagonal
Data Port	USB	Display Area	8.54" x 5.34"
Graphics input/output	USB (via DisplayLink)	Resolution	1280 x 800 pixels
Stand adjustability	Flat, 15° and 20° incline	Aspect ratio	16:10
Mounting system	VESA 75mm	Number of colors	262k
ExpressKeys	4 user-assignable	Brightness	210 cd/m ²
Power supply input	USB bus powered	Contrast ratio	800:1 (typical)
Warranty	3 years	Work surface	Completely flat glass, textured anti-glare
Tablet (Pen)		Pen	
Pen Technology	Patented electromagnetic resonance method	Type	Pressure sensitive, cordless, battery-free
Sensor Resolution	2,540 lines per inch	Switches	Tip switch, 1 side switch
Coordinate accuracy	+/- 0.5mm	Pressure levels	512
Reading height	5 mm	Tether	24" nylon fiber