

## SYSTEM SPECIFICATIONS:

### Durability Features

- \* Meets and exceeds MIL-STD 810F
- \* Water/Dust tight (IP64/IEC 60529)
- \* 42" drop
- \* Die-cast magnesium chassis
- \* Sealed I/O ports
- \* Optional Compliance with UL 1604 Class I, Division 2, Group A, B, C and D for Hazardous Locations
- \* SAE J1455 vehicle crash tested (when used with an Itronix certified vehicle dock)

### Dimensions

- \* Length: 9.65" (245 mm)
- \* Width: 11.8" (300 mm)
- \* Depth: 1.98" (50 mm)

### Weight

- \* 6.9 lbs (3.1 kg) Basic configuration

### Processor/Memory

- \* Intel® Core™2 Duo SL9400 (1.86 GHz)
- \* SMBIOS Enabled
- \* 6 MB L2 Cache
- \* 1066 MHz front-side bus
- \* 2048MB DRAM (DDR3) standard expandable to 4096MB1

### Storage

- \* 160GB 2.5" (6.35cm) 5400 RPM SATA heatedHDD2
- \* 64GB solid state drive (optional)

### Media Bay

- \* Swappable media bay accepts: MULTI DVD-RW/CD-RW, or secondary battery

### Power

- \* 7200 mA (79.9W) Lithium Ion main battery
- \* Optional 3800 mA (41.1W) Lithium Ion media bay battery pack
- \* Battery life of 8 hours with main battery, 12 hours with secondary battery
- \* Power Saver for user selectable power management optimization
- \* Hot swappable battery option
- \* ENERGY STAR® certified

### Video Graphics

- \* Intel® GMA 4500MHD

- \* 1024 MB shared DVMT 5.0 video memory

#### Display

- \* 13.3" TFT XGA outdoor viewable DynaVue® patent-pending display
- \* Outdoor viewable with DynaVue® patent pending display
- \* DynaVue® exceeds the minimum contrast ratio as required for bright sunlight per DOD-STD-3009
- \* Display heater (standard)
- \* XGA through external VGA port

#### Operating System

- \* Microsoft® Windows® XP, SP3
- \* Microsoft® Windows® Vista, SP1

#### Interfaces

- \* RJ-11 (wireline modem), and RJ-45 (ethernet LAN), 3x USB 2.0, serial port (9-pin), external video (15-pin), audio headphone (mini jack), microphone (mini jack)

#### Audio

- \* Internal microphone and (2) speakers PCI HD Audio with AC97 compliance

#### Integrated Wireline Communications

- \* 56 Kbps V. 92 fax/modem
- \* 10/100/1000M bit Ethernet LAN standard

#### Integrated Wireless Communications

- \* Up to 3 RF modems and a GPS receiver can be integrated at one time
- \* Engineered for minimum radio desense to get maximum wireless coverage
- \* Superior wireless power management
- \* MobilityXE™ software for secure wireless access and seamless roaming between your wireless or wired WAN and LAN coverage areas

#### Wireless LAN (Options)

- \* Intel® Wi-Fi Link 5100 802.11 a/b/g/draft-n network connections
- \* 2.4, 5.0 GHz dualband diversity antennas
- \* Authentication: WPA and WPA2, 802.1X (EAP-TLS, TTLS, MD5, PEAP, LEAP, EAP-FAST), EAP-SIM
- \* Encryption: 64-bit and 128-bit WEP, AES-CCMP, CKIP, TKIP

#### Wireless WAN (Options)

- \* Choice of EV-DO/1xRTT/CDMA or HSDPA/UMTS/EDGE/GSM
- \* Common Radio Module Architecture (CRMA) Express with fully integrated, field replaceable WWAN\* radio modules

- \* Integrated 800 - 2500 Ultra-Wideband antennas

\*WWAN currently only supported in North America. For country specific support, please contact your local sales representative.

#### Wireless PAN (Options)

- \* Bluetooth V 2+EDR
- \* Class 1 (100m (328ft) line-of-sight)
- \* Integrated antenna

#### GPS (Options)

- \* Fully integrated GPS
- \* Di-electrically loaded high performance quadrifilar helix antenna
- \* SiRFXTTrac high sensitivity GPS software for increased acquisition and tracking

#### Keyboard & Input

- \* Full-sized, 87-key sealed keyboard
- \* Choice of NiteVue™ glow-in-the-dark or backlit keyboard
- \* Localized versions available
- \* Capacitive Touchpad

#### Enhanced Security & Protection

- \* Password security: Pre-boot, Supervisor, User
- \* Trusted Platform Module security chip (TPM v1.2)
- \* Fingerprint reader (optional)
- \* Smart Card (CAC Card) Reader (optional)
- \* Kensington Cable lock slot
- \* Stealth mode: To boot-up without sound/light emissions
- \* Computrace® theft recovery and data protection agent in BIOS (optional)3

#### Accessories

- \* Vehicle Cradle with or w/o RF Connectors Office Dock
- \* Office Dock
- \* AC Adapter & Cord (90W )
- \* Vehicle Adapter - 12V - 24V (90W)
- \* External battery chargers
- \* Protective keyboard and display overlays
- \* Choice shoulder strap and cases
- \* Additional stylus available

#### Warranty

- \* 3 year warranty

-----

1 Total available memory will be less than 4GB. To fully utilize 4GB memory, a 64-bit enabled processor and operating system are required.

2 Actual formatted capacity varies based on preloaded devices and operating system.

3 Requires software and activation to enable theft protection.