



Integrated Tie Tags



Short or Long Run Orders • Unique Solutions • Harsh Environment Encapsulations



Part Number: WF-SM-ZT02

Size: 5.5" x .25" x .25" (12" Ziptie)

Standard Frequencies: 915 MHz UHF

Approx. Read Range: 12 ft. / 4 ft. on metal

Communication Protocol:
EPC Class 1 Generation 2

Applications: Metal Mount, Harsh Environments, Totes, Carts, Pipes

Description: Designed to be easily attached to a wide variety of containers, this tag offers exceptional read ranges and is

also metal mountable! The bendable shape and integrated zip tie make it perfect for tagging against round surfaces.

Size and frequencies can be adjusted to fit your application.



Part Number: WF-SM-ZT02

Size: 5.5" x .25" x .25" (12" Ziptie)

Standard Frequencies: 915 MHz UHF

Approx. Read Range: 12 ft.

Communication Protocol:
EPC Class 1 Generation 2

Applications: Metal Mount, Harsh Environments, Totes, Carts, Pipes

Description: Designed to be easily attached to a wide variety of containers, this tag offers exceptional read ranges! The bendable shape and integrated zip tie make it perfect for tagging against round surfaces.

Size and frequencies can be adjusted to fit your application.



Part Number: WF-SM-PT

Size: 5.5" x .75" x .5" (Var. integrated loop)

Standard Frequencies: 915 MHz UHF

Approx. Read Range:
20 ft. / 12 ft. on metal

Communication Protocol:
EPC Class 1 Generation 2

Applications: Pipelines, Metal Mount,
Warehouses

Description: Designed for use with metal pipes or other high-interference environments, this tag has an integrated rubber loop for easy attachment. Made of vulcanized rubber, it is both harsh-

environment ready and impact resistant.

Size and frequencies can be adjusted to fit your application.

Contact Information

Call today for all your custom RFID needs:

David Kennedy, VP and Gen. Mgr. Phone: (519) 268-7604;

E-mail: david.kennedy@falkensecurenetworks.com

Web: www.falkensecurenetworks.com